


OTICON | More


Fitting range*



□ OpenBass dome
■ Mold, Bass & Power dome

OSPL90 (peak)
Ear simulator 116 dB SPL
Zcc coupler 106 dB SPL


Full-on gain (peak)
Ear simulator 46 dB
Zcc coupler 36 dB



□ OpenBass dome
■ Mold, Bass & Power dome

OSPL90 (peak)
Ear simulator 127 dB SPL
Zcc coupler 117 dB SPL


Full-on gain (peak)
Ear simulator 66 dB
Zcc coupler 55 dB



■ Power Receiver Mold, Bass & Power dome

OSPL90 (peak)
Ear simulator 132 dB SPL
Zcc coupler 124 dB SPL

Full-on gain (peak)
Ear simulator 66 dB
Zcc coupler 57 dB



■ Power Receiver Mold

OSPL90 (peak)
Ear simulator 135 dB SPL
Zcc coupler 127 dB SPL

Full-on gain (peak)
Ear simulator 72 dB
Zcc coupler 64 dB

*Fitting range is based on Oticon More 1. Fitting range for Oticon More 2 & Oticon More 3 is limited to 8 kHz. Details available in Technical data sheets.

Easy, discreet miniRITE R



Oticon More miniRITE R is a discreet, rechargeable hearing aid with a lithium-ion battery and an easy to use charger.




Oticon More miniRITE R comes with groundbreaking new features and functionalities that give access to the full perspective of sounds. It is a Made for iPhone® hearing aid which also offers sound streaming direct from selected Android devices.**

Oticon More miniRITE R uses the proven miniFIT receivers and ear pieces and fits up to 105 dB HL.

**Oticon More is compatible with Android's Audio Streaming for Hearing Aids protocol (ASHA) – meaning it supports direct streaming from selected Android devices.

miniFit receivers and Power Receiver Molds

Select between three receivers with different output performance, with lengths 0-5 for non power speakers and 1-5 for power. The 105 receiver requires a custom Power Receiver Mold.



Earpieces

miniFit earpieces include standard domes, Grip Tips, MicroMold, and LiteTip. Custom earpieces are available in acrylic, soft silicone or VarioTherm® material.



OpenBass dome



Bass dome, double vent (1.4 mm)



Power dome



Grip Tip No vent



Grip Tip Vent



LiteTip



MicroMold



Power receiver mold



MicroMold, VarioTherm®



LiteTip, VarioTherm®

IP68

Proven IP68 water and dust resistant hearing aids.



C044 Silver



C091 Silver Grey



C092 Steel Grey



C063 Diamond Black



C093 Chestnut Brown



C094 Terracotta




C090 Chroma Beige



C079 Hear Pink

OTICON | More

Product comparison



TwinLink
NFMI + 2.4 GHz

oticon
life-changing technology

		More 1	More 2	More 3
Speech Understanding	MoreSound Intelligence™	Level 1	Level 2	Level 3
	- Environment configuration	5 Options	5 Options	3 Options
	- Virtual Outer Ear	3 Configurations	1 Configuration	1 Configuration
	- Spatial Balancer	100%	60%	60%
	- Neural Noise Suppression, Difficult/Easy	10 dB/4 dB	6 dB/2 dB	6 dB/0 dB
	- Sound Enhancer	3 Configurations	2 Configurations	1 Configuration
	MoreSound Amplifier™	•	•	•
	Feedback Prevention	MoreSound Optimizer™ & Feedback shield	MoreSound Optimizer™ & Feedback shield	MoreSound Optimizer™ & Feedback shield
	Spatial Sound™	4 Estimators	2 Estimators	2 Estimators
	Soft Speech Booster	•	•	•
	Frequency lowering	Speech Rescue™	Speech Rescue™	Speech Rescue™
Sound Quality	Clear Dynamics	•	•	
	Better-Ear Priority	•	•	
	Fitting Bandwidth*	10 kHz	8 kHz	8 kHz
	Bass Boost (streaming)	•	•	•
	Processing Channels	64	48	48
Listening Comfort	Transient Noise Management	4 configurations	3 configurations	3 configurations
	Wind Noise Management	•	•	•
Personalization & Optimizing Fitting	Fitting Bands	24	20	18
	Multiple Directionality options	•	•	•
	Adaptation Manager	•	•	•
	Fitting Formulas	VAC+, NAL-NL1/NAL-NL2, DSL 5.0	VAC+, NAL-NL1/NAL-NL2, DSL 5.0	VAC+, NAL-NL1/NAL-NL2, DSL 5.0
Connecting to the world	Stereo streaming (2.4 GHz)	•	•	•
	Oticon ON App & Oticon RemoteCare App	•	•	•
	ConnectClip	•	•	•
	EduMic	•	•	•
	Remote Control 3.0	•	•	•
	TV Adapter 3.0	•	•	•
	Phone Adapter 2.0 (with ConnectClip)	•	•	•
	Tinnitus SoundSupport™	•	•	•

*Bandwidth accessible for gain adjustments during fitting